



TECHNICAL INFORMATION

OEST LEICHTLAUFÖL 506 01 SAE 0W-30

Description:

Fully synthetic high-performance easy-flowing motor oil SAE 0W-30 for Otto and diesel engines for prolonged oil changing intervals. Lower fuel consumption due to reduced high temperature viscosity (HTHS).

Advantages:

Good for cold start, low fuel consumption, resistant to wear also during unfavourable operating conditions, resistant to oil mud, treating the catalyzer with care, stable in viscosity.

Qualifications:

ACEA A5/B5
 VW 503 00, 506 00, 506 01

Chemical and physical data:

colour			2,0
density	DIN 51757	g/cm ³	0,856
dyn. viscosity at 40 °C	DIN 51377	mPas	46,0
at 100 °C			7,90
kin. viscosity at 40 °C	DIN 51562	mm ² /s	55,0
at 100 °C			9,90
viscosity index		VI	168
flash point	DIN ISO 2592	°C	216
pour point	DIN ISO 3016	°C	-51

Suitable for all kinds of VW-vehicles with prolonged maintenance intervals according to the longlife concept, except Audi S3 (154 and 165 kW), RS4 (280kW), TT (165 kW) and A8 6ltr./12 cyl. (309 kW).

Edition May 2009